



Voltage	0 ~ 240VAC / 240VDC
Leads	AWG26
Contact material	gold alloy
Dielectric strength	500VAC@60Hz,60s
Insulation resistance	≥500MΩ/500VDC
Dynamic contact resistance	<100mΩ @6Vdc 50mA 5RPM
Operating Speed	0 ~ 250 rpm
Temperature	-20°C~+80°C(ET option -40°C~+80°C)
Cover material	engineering plastic
Housing material	engineering plastic
Shaft material	engineering plastic
Protection degree	IP51
Estimated life	10 ⁷ revs
Bearings	steel miniature precision ball bearings

Model	L(mm)	Ring
KS22-6x2A	19	6rings,2A/ring
KS22-12x2A	28	12rings,2A/ring
KS22-15x2A	29,5	15rings,2A/ring
KS22-18x2A	33,4	18rings,2A/ring
KS22-24x2A	41,2	24rings,2A/ring
KS22-36x2A	57	36rings,2A/ring

Max. Data Transfer Speed : 100Mbit/s

Version	Änderung / Modification Description	Dwg. No.	V35310	
			KS22	
			SERVO-DRIVE.CZ	
Die oben genannten Bemaßungen sind Richtwerte. Alle Abmessungen in mm / All dimensions in mm		Date : 21.01.2016 Author : P. UHER	Version : 1.0 Update : xx.xx.xxxx	SERVO-DRIVE.CZ