



	Rings	L
KS54-D12-6x5A	6	34
KS54-D12-12x5A	12	48
KS54-D12-18x5A	18	62
KS54-D12-24x5A	24	76

	Signal Rings
Amper	5A
Voltage	240Vac/240Vdc
Leads AWG	22
Contact material	Precious metals
Dielectric strength	500VAC@60Hz,60s
Insulation resistance	≥500MΩ/500VDC
Leads	finning PTFE
Dynamic contact resistance	<100mΩ @6Vdc 50mA 5RPM
Suggested Speed	600RPM
Temperature	-20°C~+80°C(ET option -40°C~+80°C)
Cover material	engineering plastic
Housing material	engineering plastic
Shaft material	engineering plastic
Protection degree	IP51*
Estimated life	50x10 ⁶ revs
Bearings	steel ball bearings

*Note: For IP65 option L=L+10mm and Ø21,5mm

Version	Modification Description / Änderung	Dwg. No.	V35147	KS54-D12-xxx General Drawing	
		SERVO-DRIVE.CZ			
Die oben genannten Bemassungen sind Richtwerte. Alle Abmessungen in mm / All dimensions in mm		Date: 07.07.2015	Version: 1.0	Author: P.Uher	Update: xx.xx.xxxx